

Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Reglaced version: 3.0.1, issued: 03.07.2023 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA Lawidur 2-K-PU-Klarlack, farblos sdgl. Stammlack

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

Telephone no. +49 (0)511 67490-0 Fax no. +49 (0)511 67490-20 e-mail info@einzA.com

Advice on Safety Data Sheet

sdb info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411 Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3: H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



Signal word

Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9, aromatics

Hazard statement(s)

H226 Flammable liquid and vapour.



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to

extinguish.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Add	ditional inf	formation	1	
	CAS / EC / Index / REACH no	, , , , , , , , , , , , , , , , , , , ,	Cor	ncentratio	n		%
1	Hydrocarbons, C9,	aromatics	pls.	refer to fe	ootnote (2	2)	
	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>=	25.00	- <	50.00	wt%
2	2-methoxy-1-methy	lethyl acetate					
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>=	10.00	- <	25.00	wt%
3	Reaction mass of x	ylene and ethylbenzene					
	- 905-588-0 - 01-2119488216-32	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335	>=	5.00	- <	10.00	wt%
4	2-ethoxy-1-methyle						
	54839-24-6 259-370-9 603-177-00-8 01-2119475116-39	Flam. Liq. 3; H226 STOT SE 3; H336	>=	5.00	- <	10.00	wt%



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

5	n-butyl acetate				
	123-86-4	EUH066	<	2.50	wt%
	204-658-1	Flam. Liq. 3; H226			
	607-025-00-1	STOT SE 3; H336			
	01-2119485493-29				

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	Р	-	-	-
3	-	STOT RE 2; H373: C >= 10%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.			
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9			
	List of approved workplace exposure limits (WELs) / EH40					



Trade name: einzA Lawidur 2-K-PU-Klarlack, farblos sdgl. Stammlack

Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

	1-Methoxypropylacetate				
	WEL short-term (15 min reference period)	548	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	274	mg/m³	50	ppm
	Comments	Sk			
	2000/39/EC				
	2-Methoxy-1-methylethylacetate				
	WEL short-term (15 min reference period)	550	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	275	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
2	n-butyl acetate	123-86-4		204-658-1	
2	n-butyl acetate List of approved workplace exposure limits (WELs) / l			204-658-1	
2				204-658-1	
2	List of approved workplace exposure limits (WELs) / I Butyl acetate WEL short-term (15 min reference period)		mg/m³	204-658-1 200	ppm
2	List of approved workplace exposure limits (WELs) / I Butyl acetate WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period)	EH40	mg/m³ mg/m³		ppm ppm
2	List of approved workplace exposure limits (WELs) / I Butyl acetate WEL short-term (15 min reference period)	EH40 966		200	
2	List of approved workplace exposure limits (WELs) / I Butyl acetate WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) EU 2019/1831 n-Butyl acetate	EH40 966	mg/m³	200	
2	List of approved workplace exposure limits (WELs) / I Butyl acetate WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) EU 2019/1831	EH40 966		200	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name		CAS / EC no		
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9, aroma	tics		64742-95-6	
				918-668-5	
	dermal	Long term (chronic)	systemic	12.5	mg/kg/day
	inhalative	Long term (chronic)	systemic	151	mg/m³
2	2-methoxy-1-methylethyl	acetate		108-65-6	
				203-603-9	
	dermal	Long term (chronic)	systemic	796	mg/kg/day
	inhalative	Long term (chronic)	systemic	275	mg/m³
	inhalative	Short term (acut)	local	550	mg/m³
3	Reaction mass of xylene	and ethylbenzene		-	
				905-588-0	
	dermal	Long term (chronic)	systemic	212.00	mg/kg/day
	inhalative	Short term (acut)	systemic	442.00	mg/m³
	inhalative	Short term (acut)	local	442.00	mg/m³
	inhalative	Long term (chronic)	systemic	221.00	mg/m³
	inhalative	Long term (chronic)	local	221.00	mg/m³
4	2-ethoxy-1-methylethyl ac	etate		54839-24-6	
				259-370-9	
	dermal	Long term (chronic)	systemic	103	mg/kg/day
	inhalative	Long term (chronic)	systemic	152	mg/m³
	inhalative	Short term (acut)	systemic	2366	mg/m³
5	n-butyl acetate			123-86-4	
			,	204-658-1	
	dermal	Long term (chronic)	systemic	11	mg/kg/day
	dermal	Short term (acut)	systemic	11	mg/kg/day
	inhalative	Long term (chronic)	systemic	300	mg/m³
	inhalative	Short term (acut)	systemic	600	mg/m³
	inhalative	Long term (chronic)	local	300	mg/m³
	inhalative	Short term (acut)	local	600	mg/m³

DNEL value (consumer)

No	lo Substance name			CAS / EC no)
	Route of exposure			Value	
1	1 Hydrocarbons, C9, aromatics			64742-95-6	
	• • • • • • • • • • • • • • • • • • • •			918-668-5	
	oral	Long term (chronic)	systemic	7.5	mg/kg/day
	dermal	Long term (chronic)	systemic	7.5	mg/kg/day



Trade name: einzA Lawidur 2-K-PU-Klarlack, farblos sdgl. Stammlack

Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

	inhalative	Long term (chronic)	systemic	32	mg/m³
2	2-methoxy-1-methylethyl	acetate	-	108-65-6	
				203-603-9	
	oral	Long term (chronic)	systemic	36	mg/kg/day
	oral	Short term (acut)	systemic	500	mg/kg/day
	dermal	Long term (chronic)	systemic	320	mg/kg/day
	inhalative	Long term (chronic)	systemic	33	mg/m³
	inhalative	Long term (chronic)	local	33	mg/m³
3	Reaction mass of xylene	and ethylbenzene		-	
				905-588-0	
	oral	Long term (chronic)	systemic	12.50	mg/kg/day
	dermal	Long term (chronic)	systemic	125.00	mg/kg/day
	inhalative	Short term (acut)	systemic	260.00	mg/m³
	inhalative	Long term (chronic)	systemic	65.30	mg/m³
	inhalative	Short term (acut)	local	260.00	mg/m³
	inhalative	Long term (chronic)	local	65.30	mg/m³
4	2-ethoxy-1-methylethyl ac	cetate		54839-24-6	
4				259-370-9	
4	oral	Long term (chronic)	systemic	259-370-9 13.1	mg/kg/day
4	oral dermal	Long term (chronic) Long term (chronic)	systemic	259-370-9 13.1 62	mg/kg/day
4	oral dermal inhalative	Long term (chronic) Long term (chronic) Long term (chronic)		259-370-9 13.1 62 181	mg/kg/day mg/m³
	oral dermal inhalative inhalative	Long term (chronic) Long term (chronic)	systemic	259-370-9 13.1 62 181 1420	mg/kg/day
5	oral dermal inhalative	Long term (chronic) Long term (chronic) Long term (chronic)	systemic systemic	259-370-9 13.1 62 181 1420 123-86-4	mg/kg/day mg/m³
	oral dermal inhalative inhalative n-butyl acetate	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut)	systemic systemic systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1	mg/kg/day mg/m³ mg/m³
	oral dermal inhalative inhalative n-butyl acetate oral	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic)	systemic systemic systemic systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2	mg/kg/day mg/m³ mg/m³
	oral dermal inhalative inhalative n-butyl acetate oral oral	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut)	systemic systemic systemic systemic systemic systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2	mg/kg/day mg/m³ mg/m³ mg/kg/day mg/kg/day
	oral dermal inhalative inhalative n-butyl acetate oral oral dermal	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic)	systemic systemic systemic systemic systemic systemic systemic systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2 2	mg/kg/day mg/m³ mg/m³ mg/kg/day mg/kg/day mg/kg/day
	oral dermal inhalative inhalative n-butyl acetate oral oral dermal dermal	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Short term (acut)	systemic systemic systemic systemic systemic systemic systemic systemic systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2 6 6	mg/kg/day mg/m³ mg/m³ mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/kg/day
	oral dermal inhalative inhalative n-butyl acetate oral oral dermal dermal inhalative	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic)	systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2 2 6 6 6 35.7	mg/kg/day mg/m³ mg/m³ mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/m³
	oral dermal inhalative inhalative n-butyl acetate oral oral dermal dermal inhalative inhalative	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut)	systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2 2 6 6 35.7 300	mg/kg/day mg/m³ mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/m³ mg/m³
	oral dermal inhalative inhalative n-butyl acetate oral oral dermal dermal inhalative	Long term (chronic) Long term (chronic) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic) Short term (acut) Long term (chronic)	systemic	259-370-9 13.1 62 181 1420 123-86-4 204-658-1 2 2 6 6 6 35.7	mg/kg/day mg/m³ mg/m³ mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/kg/day mg/m³

PNEC values

NI.	PNEC Values				
No	Substance name		CAS / EC no		
	ecological compartment	Туре	Value		
1	2-methoxy-1-methylethyl acetate		108-65-6		
			203-603-9		
	water	fresh water	0.635	mg/L	
	water	marine water	0.064	mg/L	
	water	fresh water sediment	3.29	mg/kg	
	with reference to: dry weight				
	water	marine water sediment	0.329	mg/kg	
	with reference to: dry weight				
	soil	-	0.29	mg/kg	
	with reference to: dry weight				
	sewage treatment plant	-	100	mg/L	
2	Reaction mass of xylene and ethylbena	zene	-		
			905-588-0		
	water	fresh water	0.327	mg/L	
	water	marine water	0.327	mg/L	
	water	fresh water sediment	12.46	mg/kg	
	water	marine water sediment	12.46	mg/kg	
	soil	-	2.31	mg/kg	
	sewage treatment plant	-	6.58	mg/L	
3	2-ethoxy-1-methylethyl acetate		54839-24-6		
			259-370-9		
	water	fresh water	2	mg/L	
	water	marine water	0.2	mg/L	
	water	Aqua intermittent	2	mg/L	



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

	water	fresh water sediment	8.2	mg/kg dry weight
	water	marine water sediment	0.82	mg/kg dry weight
	soil	-	0.67	mg/kg dry weight
	sewage treatment plant	-	62.5	mg/L
	secondary poisoning	-	117	mg/kg food
4	n-butyl acetate		123-86-4 204-658-1	
	water	fresh water	0.18	mg/L
	water	marine water	0.018	mg/L
	water	Aqua intermittent	0.36	mg/L
	water	fresh water sediment	0.981	mg/kg dry weight
	water	marine water sediment	0.0981	mg/kg dry weight
	soil	-	0.0903	mg/kg
	sewage treatment plant	_	35.6	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness>0.4mmBreakthrough time>120minAppropriate MaterialIn case of prolonged exposure: nitrile rubberMaterial thickness>0.4mmBreakthrough time>480min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	



Product no.: 0070981

Colour according to product name Odour Itel solvents	Form liquid				
Description	Colour				
like solvents					
No data available Soling point / boiling range Solvent mixture Solvent mixtu					
No data available Soling point / boiling range Solvent mixture Solvent mixtu	pH value				
Value Solvent mixture So					
Reference substance solvent mixture					
No data available			120	°C	
No data available	Melting point/freezing point				
No data available Flash point Yalue 40 - 45 °C C C C C C C C C C	No data available				
Flash point Value					
Value 40 - 45 °C					
Ignition temperature Value	Value	**	45	°C	
Value	Method	closed cup			
Reference substance solvent mixture Oxidising properties Not applicable	Ignition temperature	T	200	°C	
Not applicable			200	C	
Flammability Not applicable Lower explosion limit Value					
Not applicable	Not applicable				
Lower explosion limit Value > 0.6 % vol Reference substance solvent mixture Upper explosion limit Value < 7.5 % vol Reference substance solvent mixture Vapour pressure Value < 100 hPa Reference temperature 50 °C Reference substance solvent mixture Relative vapour density No data available Density Value 1.01 - 1.01 g/cm³ Reference temperature 20 °C Method DIN 51757 Solubility in water Comments immiscible Solubility No data available	Flammability Not applicable				
Value > 0.6 % vol Reference substance solvent mixture Upper explosion limit Value < 7.5 % vol Reference substance solvent mixture Vapour pressure < 100 hPa Reference temperature 50 °C Reference substance solvent mixture Relative vapour density No data available Relative density Value 1.01 - 1.01 g/cm³ Reference temperature 20 °C Method DIN 51757 Solubility in water Comments immiscible Solubility No data available Solubility No data available					
Upper explosion limit Value Reference substance Vapour pressure Value Reference temperature Reference substance Reference substance Reference substance Reference substance Relative vapour density No data available Relative density No data available Density Value Reference temperature DIN 51757 Solubility in water Comments I volue immiscible Solubility No data available	Value	>	0.6	% vol	
Value	Reference substance	solvent mixture			
Reference substance solvent mixture Vapour pressure Value Reference temperature Reference substance solvent mixture Relative vapour density No data available Relative density No data available Density Value 1.01 - 1.01 g/cm³ Reference temperature Density in water Comments immiscible Solubility No data available	Upper explosion limit	T.	7.5	0/	
Value			7.5	% VOI	
Value	Vapour pressure				
Reference substance solvent mixture Relative vapour density No data available Relative density No data available Density Value 1.01 - 1.01 g/cm³ Reference temperature 20 °C Method DIN 51757 Solubility in water Comments immiscible Solubility No data available	Value	<			
Relative density No data available Density Value Reference temperature Method DIN 51757 Solubility in water Comments Solubility No data available	Reference substance	solvent mixture	50	C	
Relative density No data available Density Value Reference temperature Method DIN 51757 Solubility in water Comments Immiscible Solubility No data available					
No data available Density	No data available				
Value Reference temperature Method DIN 51757 Solubility in water Comments immiscible Solubility No data available	Relative density No data available				
Reference temperature 20 °C Method DIN 51757 Solubility in water Comments immiscible Solubility No data available					
Method DIN 51757 Solubility in water Comments immiscible Solubility No data available		1.01 -			
Comments immiscible Solubility No data available		DIN 51757	20		
Solubility No data available					
No data available	Comments	immiscible			
	Solubility No data available				
CONTROL CONTROL INCUMENTATION VALUE TO CONTROL		10)			
No Substance name CAS no. EC no.			S no.		EC no.



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

1	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
log F	Pow			1.2		
Refe	erence temperature			20	°C	
Meth	Method OECI					
Soul	rce	ECHA				
2	2-ethoxy-1-methylethyl acetate		54839-24-6		259-370-9	
log F	Pow			0.76		
Refe	Reference temperature			22	°C	
with	with reference to pH 7					
Soul	rce	ECHA				
3	n-butyl acetate		123-86-4		204-658-1	
log F	Pow			2.3		
Refe	erence temperature			25	°C	
Meth	nod	OECD 117				
Soul	rce	ECHA				

Kinematic viscosity					
Value	19 - 21	sec			
Reference temperature	20	°C			
Method	DIN EN 2431 (6 mm)				

Solvent separation test					
Value	<	3	%		
Reference temperature		20	°C		

Particle characteristics	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acu	Acute oral toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9, aromatics		64742-95-6		918-668-5	
LD5	0	>		3492	mg/kg bodyweight	
Spe		rat				
Sou	rce	ECHA				
2	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
LD5	0			5155	mg/kg bodyweight	
Spe	cies	rat				



Trade name: einzA Lawidur 2-K-PU-Klarlack, farblos sdgl. Stammlack

Product no.: 0070981

Method Source	OECD 401 ECHA			
3 n-butyl acetate		123-86-4		204-658-1
LD50			10760	mg/kg bodyweight
Species	rat			
Method	OECD 423			
Source	ECHA			

Acu	Acute dermal toxicity (result of the ATE calculation for the mixture)				
No	Product Name				
1	einzA Lawidur 2-K-PU-Klarlack, farblos sdgl.				
	Stammlack				
Con	nments	The result of the applied calculation method according to the			
		European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part			
		3 of Annex I is outside the values that imply a classification / labelling			
		of this mixture according to table 3.1.1 defining the respective			
		categories (ATE dermal > 2000 mg/kg).			

Acu	Acute dermal toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9, aromatics		64742-95-6		918-668-5	
LD5	0	>		3160	mg/kg bodyweight	
Spe	cies	rabbit				
Meth	nod	OECD 402				
Soul	rce	ECHA				
2	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
LD5	0	>		5000	mg/kg bodyweight	
Spe	cies	rat				
Meth	nod	OECD 402				
Soul	rce	ECHA				
3	n-butyl acetate		123-86-4		204-658-1	
LD5	0	>		14112	mg/kg bodyweight	
Spe	cies	rabbit				
Metl	nod	OECD 402				
Soul	rce	ECHA				

Acu	Acute inhalational toxicity (result of the ATE calculation for the mixture)					
No	Product Name	Product Name				
1	einzA Lawidur 2-K-PU-Klarlack, farblos s	einzA Lawidur 2-K-PU-Klarlack, farblos sdgl.				
	Stammlack					
Com	iments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).				

Acu	te inhalational toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9, aromatics		64742-95-6		918-668-5	
LC5	0	>		6.193	mg/l	
Dura	ation of exposure			4	h	
		Vapour				
Species		rat				
Meth	nod	OECD 403				
Soul	rce	ECHA				
Eval	uation/classification	Based on av	ailable data, the	classification	on criteria are not met.	
2	2-ethoxy-1-methylethyl acetate		54839-24-6		259-370-9	
LC5	0	>		6.99	mg/l	
Dura	ation of exposure			4	h	
State	e of aggregation	Dust/mist				
Spe	cies	rat				
Meth	nod	OECD 403				



Trade name: einzA Lawidur 2-K-PU-Klarlack, farblos sdgl. Stammlack

Product no.: 0070981

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Skir	Skin corrosion/irritation					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9, aromatics		64742-95-6		918-668-5	
Spe	cies	rabbit				
Metl	nod	OECD 404				
Sou	rce	ECHA				
Eva	luation	low-irritant				
Eva	luation/classification	Based on ava	ailable data, the clas	sification	criteria are not met.	
2	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
Spe	cies	rabbit				
Metl	nod	OECD 404				
Sou	rce	ECHA				
Eva	luation	non-irritant				
3	2-ethoxy-1-methylethyl acetate		54839-24-6		259-370-9	
Dura	ation of exposure		4		h	
Spe	cies	rabbit				
Metl	nod	OECD 404				
Sou	rce	ECHA				
Eva	luation	non-irritant				
Eva	luation/classification	Based on ava	ailable data, the clas	sification	criteria are not met.	
4	n-butyl acetate		123-86-4		204-658-1	
Spe	cies	rabbit				
Metl	nod	OECD 404				
Sou	rce	ECHA				
Eva	luation	non-irritant				

Seri	Serious eye damage/irritation			
No	Substance name		CAS no.	EC no.
1	Hydrocarbons, C9, aromatics		64742-95-6	918-668-5
Spe	cies	rabbit		
Meth	nod	OECD 405		
Soul	rce	ECHA		
Eval	uation	non-irritant		
2	2-methoxy-1-methylethyl acetate		108-65-6	203-603-9
Spe	cies	rabbit		
Meth	nod	OECD 405		
Soul	rce	ECHA		
Eval	uation	non-irritant		
3	2-ethoxy-1-methylethyl acetate		54839-24-6	259-370-9
Spe	cies	rabbit		
Meth	nod	OECD 405		
Soul	rce	ECHA		
Eval	uation	non-irritant		
Eval	uation/classification	Based on ava	ailable data, the classification	ı criteria are not met.
4	n-butyl acetate		123-86-4	204-658-1
Spe	cies	rabbit		
Method		OECD 405		
Source		ECHA		
Eval	uation	non-irritant		

Respiratory or skin sensitisation		
No Substance name	CAS no.	EC no.
1 Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Route of exposure	Skin	
Species	guinea pig	
Method	OECD 406	
Source	ECHA	
Evaluation	non-sensitizing	
2 2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure	Skin	



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
3 2-ethoxy-1-methylethyl acetate	54839-24-6 259-370-9
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
Evaluation/classification	Based on available data, the classification criteria are not met.

Ger	Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.	
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5	
Sou	rce	ECHA		
Eva	luation/classification	Based on available data, the classification	r criteria are not met.	
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	
Туре	e of examination	in vitro gene mutation study in bacteria		
Met	nod	OECD 471		
Sou	rce	ECHA		
Eva	luation/classification	Based on available data, the classification criteria are not met.		
3	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9	
Туре	e of examination	in vitro gene mutation study in bacteria		
Spe	cies	Salmonella typhimurium		
Metl	nod	OECD 471		
Source		ECHA		
Evaluation/classification		Based on available data, the classification	r criteria are not met.	
4	n-butyl acetate	123-86-4	204-658-1	
Sou	rce	ECHA		
Eval	luation/classification	Based on available data, the classification	riteria are not met.	

Rep	Reproduction toxicity				
No	Substance name	CAS no.	EC no.		
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5		
Source		ECHA			
Evaluation/classification		Based on available data, the classification	r criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1		
Source		ECHA			
Evaluation/classification		Based on available data, the classification	r criteria are not met.		

Carcinogonicity	
Carcinogenicity	
No data available	

STOT - single exposure No data available

STOT - repeated exposure			
No Substance name	CAS no.	EC no.	
1 2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	
Route of exposure	oral		
Species	rats (male/female)		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2 2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9	
Route of exposure	dermal		
Duration of exposure	3	months	
Species	rabbit		
Method	OECD 411		
Source	ECHA		
Evaluation/classification	Based on available data, the classification	n criteria are met.	
3 n-butyl acetate	123-86-4	204-658-1	
Route of exposure	inhalational		



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

NOAEC		500	ppm
Duration of exposure		90	day(s)
Species	rat		• , ,
Method	EPA OTS 798.2450		
Source	ECHA		
Evaluation/classification	Based on available data, the	classification criteria	a are not met.

Aspiration hazard	
No data available	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxi	Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.	
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5	
LL50)	9	.2 mg/l	
Dura	ation of exposure	9	6 h	
Spe		Oncorhynchus mykiss		
Meth		OECD 203		
Sou	•	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	
LC5			80 mg/l	
	ation of exposure	9	6 h	
Spe		Oncorhynchus mykiss		
Meth		OECD 203		
Sou	•	ECHA		
3	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9	
LC5			40 mg/l	
	ation of exposure	9	6 h	
Spe		Oncorhynchus mykiss		
Meth		OECD 203		
Sou		ECHA		
	uation/classification	Based on available data, the cla		
4	n-butyl acetate	123-86-4	204-658-1	
LC5		1		
	ation of exposure	9	6 h	
Spe		Pimephales promelas		
Method		OECD 203		
Sou		ECHA		
Evaluation/classification		Based on available data, the cla	ssification criteria are not met.	

Toxicity to fish (chronic)	
Toxicity to fish (chilofile)	
No data available	
No data available	



Product no.: 0070981

Toxi	city to Daphnia (acute)			
No	Substance name	CAS no.		EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6		918-668-5
EL5	0		3.2	mg/l
	ation of exposure		48	h
Spe		Daphnia magna		
Meth		OECD 202		
Soul		ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6		203-603-9
EC5		>	500	mg/l
	ation of exposure		48	h
		Daphnia magna		
Meth		EU Method C.2		
Soul		ECHA		
3	2-ethoxy-1-methylethyl acetate	54839-24-6		259-370-9
EC5			110	mg/l
	ation of exposure		48	h
Spe		Daphnia magna		
Meth		OECD 202		
Soul		ECHA		
Eval	uation/classification	Based on available data, the	e classificatior	
4	n-butyl acetate	123-86-4		204-658-1
EC5			44	mg/l
	ation of exposure		48	h
Spe		Daphnia magna		
Soul	·	ECHA		
Eval	uation/classification	Based on available data, the	e classification	n criteria are not met.

Toxi	city to Daphnia (chronic)				
No	Substance name	CAS no.		EC no.	
1	2-methoxy-1-methylethyl acetate	108-65-6		203-603-9	
NOE	EC	>=	100	mg/l	
Dura	ation of exposure		21	day(s)	
Spe	cies	Daphnia magna			
Method		OECD 211			
Sou	rce	ECHA			
2	n-butyl acetate	123-86-4		204-658-1	
NOE	EC .		23	mg/l	
Dura	ation of exposure		21	day(s)	
Spe	cies	Daphnia magna			
with	reference to	CAS 110-19-0			
Meth	nod	OECD 211			
Sou	rce	ECHA			
Eval	uation/classification	Based on available data,	the classification	on criteria are not met.	

Toxicity to algae (acute)		
No Substance name	CAS no.	EC no.
1 Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50	2	.9 mg/l
Duration of exposure	7	2 h
Species	Pseudokirchneriella subcapitata	ì
Method	OECD 201	
Source	ECHA	
2 2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	> 1	000 mg/l
Duration of exposure	9	6 h
Species	Raphidocelis subcapitata	
Method	OECD 201	
Source	ECHA	
3 2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
EC50	> 1	00 mg/l
Duration of exposure	7	2 h



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

Species
Method
Source
Evaluation/classification

Desmodesmus subspicatus
OECD 201
ECHA
Based on available data, the classification criteria are not met.

Toxicity to algae (chronic)

No data available

Bact	Bacteria toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9, aromatics		64742-95-6		918-668-5	
EC5	0	>		99	mg/l	
Dura	tion of exposure			10	min	
Spec	cies	activated slud	lge			
Meth	nod	OECD 209				
Sour	rce rce	ECHA				
2	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
EC1	0	>		1000	mg/l	
Dura	tion of exposure			30	min	
Spec	cies	activated slud	lge			
Meth	nod	OECD 209				
Sour	ce	ECHA				
3	n-butyl acetate		123-86-4		204-658-1	
IC50				356	mg/l	
Dura	tion of exposure			40	h	
Spec	cies	Tetrahymena	pyriformis (Pro	tozoa)		
Sour	ce	ECHA				

12.2 Persistence and degradability

Biod	Biodegradability						
No	Substance name	CAS no.		EC no.			
1	Hydrocarbons, C9, aromatics	64742-95-6		918-668-5			
Туре		BSB					
Valu	e		78	%			
Dura			28	d			
Meth		OECD 301 F					
Sour		ECHA					
	uation	readily biodegradable					
2	2-methoxy-1-methylethyl acetate	108-65-6		203-603-9			
Туре		aerobic biodegradation					
Valu			83	%			
Dura			28	day(s)			
Meth		OECD 301 F					
Sour		ECHA					
	uation	readily biodegradable					
3	2-ethoxy-1-methylethyl acetate	54839-24-6		259-370-9			
Туре		aerobic biodegradation					
Valu			100	%			
Dura			28	d			
Meth		OECD 301 D					
Sour		ECHA					
	uation	readily biodegradable					
4	n-butyl acetate	123-86-4		204-658-1			
Турє		aerobic biodegradation					
Valu			83	%			
Dura			28	day(s)			
Meth		OECD 301 D					
Sour		ECHA					
Eval	uation	readily biodegradable					

Abiotic Degration					
No	Substance name	CAS no.	EC no.		
1	n-butyl acetate	123-86-4	204-658-1		



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

Туре	Photolysis		
Half-life		3.3	day(s)
Reference temperature		25	°C
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)					
No	Substance name	CAS no.	EC no.		
1	n-butyl acetate	123-86-4	204-658-1		
BCF		15.3			
Method		Calculation model used (Q)SAR			
		ECHA			

Partition coefficient n-octanol/water (log value)						
No	Substance name		CAS no.		EC no.	
1	2-methoxy-1-methylethyl acetate		108-65-6		203-603-9	
log F	Pow			1.2		
Refe	erence temperature			20	°C	
Meth	nod	OECD 117				
Soul	rce	ECHA				
2	2-ethoxy-1-methylethyl acetate		54839-24-6		259-370-9	
log F	Pow			0.76		
Refe	erence temperature			22	°C	
with	reference to	pH 7				
Soul	rce	ECHA				
3	n-butyl acetate		123-86-4		204-658-1	
log F	Pow			2.3		
Refe	erence temperature			25	°C	
Meth	nod	OECD 117				
Soul	rce	ECHA				

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

 Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information	
Do not allow to enter drains or water courses.	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group III
Hazard identification no. 30
UN number UN1263
Proper shipping name PAINT
Tunnel restriction code D/E

l ahel 3

Environmentally hazardous Symbol "fish and tree"

substance mark

14.2 Transport IMDG

Class 3
Packing group III
UN number UN1263
Proper shipping name PAINT

Technical name Hydrocarbons, C9, aromatics

EmS F-E+S-E

Label 3

Marine pollutant mark Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class 3
Packing group III
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40



Product no.: 0070981

Current version: 3.0.2, issued: 03.01.2024 Replaced version: 3.0.1, issued: 03.07.2023 Region: GB

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

E2, P5c

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)	
VOC content	61.35 %

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P The harmonised classification as a carcinogen applies unless the full refining history is

known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation

shall be performed also for that hazard class.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 696612